



TM

Verieter
SPA

PRODUCT LINE

LOADERS
TELESCOPIC WHEEL LOADERS
BACKHOE TOOL CARRIERS





Venieri 75

SPA 1948-2023

New fully-equipped plant opens.



1948



Ferdinando and Carlo Venieri create the first **Venieri crawler tractor**.

Production of **earthmoving machines** begins.



1954



Venieri starts co-operation with **Perkins** engine manufacturer.

Venieri introduces the **world's first hydrostatic transmission** in earthmoving machines.



1956

1960



Production of **hydrostatic forklift** begins.

Actual **main plant** opens.



1962

1968



Venieri becomes a **Limited Company (L.T.D.)** strengthening his name on the domestic market.

Production of the **rigid type** of Backhoe Loader **discontinued**.



1974

1980



Introduction of a **new type of backhoe loader**.

Installation of **Hydrostatic transmission** begins in **all machines**.



1986

1992



Venieri patented the world's **first electrical backhoe loader**.

75 Worldwide Partners reached.



1999

2002




100% Green Power Company.

70th ANNIVERSARY. QUALITY MEETS HISTORY.



2010

2012



Venieri begins introducing **TIER 4F** engines.

Complete **restyling** of **Company main Headquarters**.



2016

2018



Entire range now featuring **TIER 4F** engines.

2021

2023

WHEEL LOADERS



13.63C

Linkage	"Z" BAR
Engine Max Power	184 HP
Engine Emission	TIER 4f - DEF
Breakout Force	26,455 lbs
Static Tipping Load, Full Turn	21,164 lbs
Bucket Capacity, Min/Max	3.5 - 3.9 cu/yd
Max Permissible Weight	31,195 lbs
Tyres	20,5 R25
Forks Load Capacity (EN 474-3)	12,346 lbs
Max Speed	25 mph



10.63D

Linkage	PARALLEL
Engine Max Power	143 HP
Engine Emission	TIER 4f - DEF
Breakout Force	17,637 lbs
Static Tipping Load, Full Turn	11,464 lbs
Bucket Capacity, Min/Max	2.3 - 2.9 cu/yd
Max Permissible Weight	22,289 lbs
Tyres	17,5 x 25
Forks Load Capacity (EN 474-3)	7,496 lbs
Max Speed	25 mph



9.63D

Linkage	"Z" BAR
Engine Max Power	143 HP
Engine Emission	TIER 4f - DEF
Breakout Force	18,960 lbs
Static Tipping Load, Full Turn	12,125 lbs
Bucket Capacity, Min/Max	2.3 - 2.9 cu/yd
Max Permissible Weight	22,289 lbs
Tyres	17,5 x 25
Forks Load Capacity (EN 474-3)	8,113 lbs
Max Speed	25 mph



8.63C HL

Linkage	PARALLEL
Engine Max Power	128 HP
Engine Emission	TIER 4f - DEF
Breakout Force	20,723 lbs
Static Tipping Load, Full Turn	10,141 lbs
Bucket Capacity, Min/Max	1,6 cu/yd
Max Permissible Weight	19,290 lbs
Tyres	460/70 R24
Forks Load Capacity (EN 474-3)	6,173 lbs
Max Speed	25 mph



7.63D

Linkage	"Z" BAR
Engine Max Power	128 HP
Engine Emission	TIER 4f - DEF
Breakout Force	20,062 lbs
Static Tipping Load, Full Turn	11,023 lbs
Bucket Capacity, Min/Max	1.8 - 2.6 cu/yd
Max Permissible Weight	19,290 lbs
Tyres	15,5 x 25
Forks Load Capacity (EN 474-3)	6,614 lbs
Max Speed	25 mph



5.63D

Linkage	"Z" BAR
Engine Max Power	79 HP
Engine Emission	TIER 4f
Breakout Force	14,110 lbs
Static Tipping Load, Full Turn	9,700 lbs
Bucket Capacity, Min/Max	1.4 - 2.0 cu/yd
Max Permissible Weight	13,823 lbs
Tyres	405/70 R20
Forks Load Capacity (EN 474-3)	5,997 lbs
Max Speed	25 mph



4.63H

Linkage	"Z" BAR
Engine Max Power	72 HP
Engine Emission	TIER IVf
Breakout Force	12,346 lbs
Static Tipping Load, Full Turn	9,259 lbs
Bucket Capacity, Min/Max	1.3 - 2.0 cu/yd
Max Permissible Weight	13,669 lbs
Tyres	16/70 x 20
Forks Load Capacity (EN 474-3)	5,644 lbs
Max Speed	25 mph



2.63D Plus

Linkage	"Z" BAR
Engine Max Power	53 HP
Engine Emission	TIER 4f
Breakout Force	11,685 lbs
Static Tipping Load, Full Turn	6,614 lbs
Bucket Capacity, Min/Max	1.0 - 1.6 cu/yd
Max Permissible Weight	10,582 lbs
Tyres	12,0/75 x 18
Forks Load Capacity (EN 474-3)	4,233 lbs
Max Speed	17 mph



1.63D

Linkage	"VZPK"
Engine Max Power	53 HP
Engine Emission	TIER 4f
Breakout Force	8,466 lbs
Static Tipping Load, Full Turn	4,079 lbs
Bucket Capacity, Min/Max	0.65 - 1.0 cu/yd
Max Permissible Weight	7,937 lbs
Tyres	12 - 16,5
Forks Load Capacity (EN 474-3)	2,434 lbs
Max Speed	25 mph



1.33C

Linkage	PARALLEL
Engine Max Power	53 HP
Engine Emission	TIER 4f
Breakout Force	5,071 lbs
Static Tipping Load, Full Turn	4,409 lbs
Bucket Capacity, Min/Max	0.6 cu/yd
Max Permissible Weight	9,105 lbs
Tyres	12 - 16,5
Forks Load Capacity (EN 474-3)	2,646 lbs
Max Speed	12 mph



TELESCOPIC WHEEL LOADERS

8.63TL

Linkage	TELESCOPIC ARM
Engine Max Power	143 HP
Engine Emission	TIER IVf - DEF
Max Load Height with Forks - Telescopic Extended	17'4"
Bucket Capacity, Min/Max	1.6 cu/yd
Max Permissible Weight	20,062 lbs
Tyres	460/70 R24
Forks Load Capacity (EN 474-3)	7,055 lbs
Max Speed	25 mph



1.63D TL

Linkage	TELESCOPIC ARM
Engine Max Power	53 HP
Engine Emission	TIER 4f
Max Load Height with Forks - Telescopic Extended	12'2"
Bucket Capacity, Min/Max	0.65 cu/yd
Max Permissible Weight	8,818 lbs
Tyres	31X15,50 - 15,3
Forks Load Capacity (EN 474-3)	2,756 lbs
Max Speed	25 mph

BACKHOE TOOL CARRIERS



8.23G

Linkage	"Z" BAR	"Z" BAR
Engine Max Power	106 HP	106 HP
Engine Emission	TIER 4f - DEF	TIER 4f - DEF
Breakout Force	15,212 lbs	23,810 lbs
Static Tipping Load, Full Turn	11,574 lbs	13,558 lbs
Bucket Capacity, Min/Max	1.4 - 1.8 cu/yd	1.7 - 2.6 cu/yd
Max Permissible Weight	18,717 lbs	21,870 lbs
Tyres	16/70 x 24	17,5L x 24
Forks Load Capacity (EN474-3)	6,878 lbs	8,554 lbs
Max Speed	25 mph	25 mph
Max Digging Depth, Std./Telescopic	15'1" - 17'9"	16'5" - 19'8"

10.23E



1.33C

Linkage	PARALLEL
Engine Max Power	53 HP
Engine Emission	TIER 4f
Breakout Force	5,071 lbs
Static Tipping Load, Full Turn	4,409 lbs
Bucket Capacity, Min/Max	0.6 cu/yd
Max Permissible Weight	9,105 lbs
Tyres	12 - 16,5
Forks Load Capacity (EN474-3)	2,646 lbs
Max Speed	12 mph
Max Digging Depth, Std./Telescopic	9'0" - 10'8"



www.venieriamerica.com



Via Piratello, 106 - 48022 Lugo (RA) - ITALY
 Tel. +39 0545 904411 Fax +39 0545 30389
 e-mail: info@vf-venieri.com | www.vf-venieri.com

Spare Parts
 Tel. +39 0545 904429 Fax +39 0545 24555
 e-mail: ricambi@vf-venieri.com